

NEMA 4X Vapour Tight



Ideal for parking structures, paint lines, and parts inspections



*Suitable for damp/wet locations or wherever a high impact-resistant fixture is required

NEMA 4X Series Vapour Tight

PRODUCT #	WATTS	VOLTAGE	CCT	LUMENS	LENGTH	CTN QTY
VT4-36W-M40K-UD	36W	120-347V	4000K	4,605 lm	4 ft	4
VT4-36W-M50K-UD	36W	120-347V	5000K	4,680 lm	4 ft	4
VT4-46W-M3CK-UD	46W	120-347V	3500K, 4000K, 5000K,	5,950 lm	4 ft	4
VT4-65W-M3CK-UD	65W	120-347V	3500K, 4000K, 5000K	8,643 lm	4 ft	4
VT4-100W-A50K-UD	100W	120-347V	5000K	13,750 lm	4 ft	1
VT8-100W-A50K-UD	100W	120-347V	5000K	14,600 lm	8 ft	1
VT4-150W-A50K-UD	150W	120-347V	5000K	20,400 lm	4 ft	1

STVT-IMS	Microwave Motion Sensor (Can be mounted at a maximum height of 4 meters)
VTHB-IMS	Microwave Motion Sensor for VT4 and VT8 (Can be mounted over 4 meters)
STVT-8W-EBU	Emergency Battery Backup Kit (120-277V only)

Emergency Battery Backup Kit (120-277V)
(ordered separately)

Vapour Tight Linear Fixture
8 ft

Microwave Motion Sensor Internally Mounted & Dimmable
(ordered separately)



STVT-8W-EBU



VT8-100W-A50K-UD



STVT-IMS