


Mini Flood Light

15W | 4000K | 120-277V | Yoke Mount

Ideal for landscaping, patio, and security lighting, signs, and building facades
Excellent replacement for quartz halogen fixtures



Suggested Substitutions:
FLM-15W-40K-LV-KN 

TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	1,603 lm
Efficacy	111.05 lm/W
CCT	4000K
CRI	80
L70 Life	50,000 hrs
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E482965
-----	---------

DIMENSIONS



ISOCANDELA



ELECTRICAL

Wattage	15W
Voltage	120-277V
Power Factor	0.9
THD	18.39%
Operating Temp	-40 to 50°C

CONSTRUCTION

Housing	Aluminum Alloy
Finish	Bronze
IP Rating	IP65
Carton Weight	10.4 kg
Carton Qty	8
Carton Dimensions	484 x 302 x 297 mm

SUGGESTED SUBSTITUTION

FLM-15W-40K-LV-KN

ILLUMINANCE AT A DISTANCE

Distance	Illuminance at a Distance	
	Center Beam fc	Beam Width
17.0ft	2.07 fc	50.5 ft 45.1 ft
34.0ft	0.52 fc	101.1 ft 90.2 ft
51.0ft	0.23 fc	151.6 ft 135.3 ft
68.0ft	0.13 fc	202.2 ft 180.4 ft
85.0ft	0.08 fc	252.7 ft 225.6 ft
102.0ft	0.06 fc	303.3 ft 270.7 ft

■ Vert. Spread: 112.1°
■ Horiz. Spread: 106.0°