

2'x 4' Premium Panel

30W, 40W, 50W Selectable | Colour Tunable | 120-347V

High performance, light-weight luminaires suitable for lay-in, surface or pendant mounting. Ideal for use in schools, health care applications, offices, retail spaces, and more

0-10V Dimming Lead on Both Sides of Driver Junction Box

Use Switches to Select Colour Temperature and Wattage

Non-yellowing Frosted Lens



Wattage Selectable
(30W / 40W / 50W)



CCT Tunable
(3000K / 3500K / 4000K)



120-347V, 0-10V Dimmable Driver



Less than 1.8" Deep
ideal for tight plenum areas

Seismic Clips Included



Waffle Stamping
increases heat dissipation and driver life



Junction Box (PLS-JB)
sold separately

Accessories (Sold Separately)



Suspension Kit
PLS-SUSKIT



Surface Mount Kit
PLS24-SK



Junction Box
PLS-JB



Recessed Frame Kit
PLS24-RFK

TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	6,250 lms @ 3000K
Efficacy	125 lm/W
CCT	Tunable (30K/35K/40K)
CRI	80
Dimmable	0-10V
Beam Angle	120°
L70 Life	50,000 hrs
Warranty	7-year

APPROVALS AND LISTINGS

ETL	5000444
-----	---------

ISOCANDELA PLOT



ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Width	
17.0ft	7.05 fc	52.4 ft	52.1 ft
34.0ft	1.76 fc	104.7 ft	104.2 ft
51.0ft	0.78 fc	157.1 ft	156.3 ft
68.0ft	0.44 fc	209.5 ft	208.4 ft
85.0ft	0.28 fc	261.9 ft	260.5 ft
102.0ft	0.20 fc	314.2 ft	312.6 ft

■ Vert. Spread: 114.0°
■ Horiz. Spread: 113.7°

ELECTRICAL

Wattage	Selectable (30W/40W/50W)
Voltage	120-347V
Power Factor	0.9
THD	6%
Operating Temp	-20 to 40°C

CONSTRUCTION

Housing	Metal
Finish	White
IP Rating	IP20
Product Dimensions	23.75 x 47.72 x 1.67 in
Carton Qty	4

ACCESSORIES (SOLD SEPARATELY)

PLS24-SK	Surface Mount Kit
PLS24-RFK	Recessed Frame Kit
PLS-SUSKIT	Suspension Kit
PLS-JB	Junction Box

DIMENSIONAL DRAWINGS (IN)

