

# Pole Top Area Light

55W | CCT Tunable | 120-277V



Elegant look and design

Ideal for parking lots, pathways, parks, retail settings, and more

Colour Tunable  
3000K / 4000K / 5000K

Twist Lock Photocell Receptacle  
and Photocell Included  
Shorting cap sold separately

Polyester  
Powder-Coat Finish  
(Bronze)

High Efficiency Optics  
with type 5 distribution

Fits Up To 3" OD pole



Approved by International  
Dark Sky Association  
when set for 3000K operation



JL-208

Optional Accessories (sold separately)  
Shorting Cap (JL-208)

## TECHNICAL DATA




### LIGHT SPECIFICATIONS

Lumens	6,214 lm @ 3000K
Efficacy	113.52 lm/W
CCT	3000K / 4000K / 5000K
CRI	80
Distribution	90°
L70 Life	50,000 hours
Warranty	10-year

### APPROVALS AND LISTINGS

cUL	E482965
DLC	PL7PCEYMLZFP

### ISOCANDELA PLOT



\*Plotted at 3000K

### ILLUMINANCE AT A DISTANCE

Center Beam fc	Beam Width	
17.0ft	10.4 ft	29.6 ft 22.5 ft
34.0ft	2.59 fc	59.1 ft 45.0 ft
51.0ft	1.15 fc	88.7 ft 67.5 ft
68.0ft	0.65 fc	118.3 ft 90.0 ft
85.0ft	0.41 fc	147.8 ft 112.5 ft
102.0ft	0.29 fc	177.4 ft 135.0 ft

■ Vert. Spread: 82.0°  
■ Horiz. Spread: 67.0°

### ELECTRICAL

Wattage	55W
Voltage	120-277V
Power Factor	0.9
THD	15%
Operating temp	-40 to 60°C

### CONSTRUCTION

Housing	Aluminum alloy
Finish	Polyester powder-coat
Colour	Bronze
IP rating	IP65
Weight	14.33 lbs
Carton qty	1

### ACCESSORIES (SOLD SEPARATELY)

Shorting Cap	JL-208
--------------	--------

### DIMENSIONS

