

200W



AREA / FLOOD LIGHT



Ideal for outdoor applications such as parking lots, construction sites, storage and rail yards, industrial locations, marinas, billboard/sign illumination, and more

121+ LM/W



Quick Change Mounting Options (additional cost): Slip Fitter, Round Pole Arm, or Square Pole Arm



TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	23,835 lm
Efficacy	121.47 lm/W
CCT	4000K
Distribution	Type III, Type II + V optional
CRI	83.5
Dimmable	0-10V
Warranty	10-year


APPROVALS AND LISTINGS

cUL	E352127
DLC PREMIUM	PLAQNFYUXS8F

DIMENSIONS



ISOCANDELA PLOT



ILLUMINANCE AT A DISTANCE

Illuminance at a Distance				
	Center Beam fc	Beam Wi	dth	
17.0 R	20.7 fc	42.5 ft	92.3 ft	
34.08	5.17 fc	85.0 ft	184.6 ft	
51.0R	2.30 fc	127.5 ft	276.9 ft	
68.08	1.29 fc	170.0 ft	369.3 ft	
85.0R	0.83 fc	212.5 ft	461.6 ft	
102.0ft	0.57 fc	255.0 ft	553.9 ft	
	Vert. Spread: 102.7° Horiz. Spread: 139.6°			

ELECTRICAL

Wattage	200W
Voltage	100-277V
Power factor	0.96
THD	6.24%
Operating temp	-40 to 40° C

CONSTRUCTION

Housing	Die cast aluminum
Finish	Anodized finish
Colour	Bronze / White available
IP rating	IP65
Weight	15.44 lbs
Carton qty	1

MOUNTING OPTIONS



Complete with Standard Trunnion Mount Product #: FL03-200W-40K



Optional Adjustable Slip Fit Mount Product #: FL03-TA (Available at an additional cost)



Optional Round Pole Arm Mount Product #: FL03-TB (Available at an additional cost)



Optional Square Pole Arm Mount Product #: FL03-TC (Available at an additional cost)



Photocell sensor available Product #: FL03-PC (Available at an additional cost)

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com