

# 150W High Bay, 120-277V



NEW HB7 series High Bay Ideal for warehouses, factories, and workshops

Product #



High grade aluminum body for superior heat dissipation

Optical grade high impact glass for maximum light transmittance (110° beam angle)

1m power cord extension available



# **TECHNICAL DATA**






## LIGHT SPECIFICATIONS

| Lumens   | 18,434 lm   |
|----------|-------------|
| Efficacy | 130.46 lm/W |
| CCT      | 4000K       |
| CRI      | 82.1        |
| L70 Life | 60,000 hrs  |
| Dimmable | 0-10V       |
| Warranty | 5-year      |


# APPROVALS AND LISTINGS

| cUL         | E482965      |
|-------------|--------------|
| DLC Premium | PL18S7WKJIG7 |

#### LUMINOUS INTENSITY DISTRIBUTION CURVE



### AVERAGE ILLUMINANCE EFFECTIVE FIGURE




# **ELECTRICAL**

| Wattage        | 150W        |
|----------------|-------------|
| Voltage        | 120-277V    |
| Power factor   | 0.93        |
| THD            | 10.76%      |
| Operating temp | -30 to 50°C |

# CONSTRUCTION

| Housing           | Aluminum alloy     |
|-------------------|--------------------|
| Finish            | Black              |
| IP rating         | IP65               |
| Weight            | 7.05 lbs           |
| Carton qty        | 1                  |
| Carton weight     | 9.25 lbs           |
| Carton dimensions | 360 x 360 x 195 mm |

# **DIMENSIONS**



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

