

200W High Bay, 277-480V



NEW HB7 series High Bay
Ideal for warehouses, factories, and workshops



High grade aluminum body for superior heat dissipation

110° beam angle

high impact glass for maximum light transmittance

1m power cord extension available



TECHNICAL DATA





LIGHT SPECIFICATIONS

Lumens	27,610 lm
Efficacy	138.39 lm/W
CCT	5000K
CRI	80
L70 Life	60,000 hrs
Dimmable	0-10V
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLM877MPKT3D

ILLUMINANCE AT A DISTANCE

C	enter Beam fc 💎	Beam Wi	idth
17.0ft	33.2 fc 🔏	53.7 ft	53.1 ft
34.0ft	8.31 fc	107.3 ft	106.2 ft
51.0R	3.69 fc	161.0 ft	159.3 ft
68.0ft	2.08 fc	214.6 ft	212.4 ft
85.0 R	1.33 fc	268.3 ft	265.5 ft
102.0ft	0.92 fc	321.9 ft	318.6 ft
	:. Spread: 115.3 iz. Spread: 114.7		

ISOCANDELA PLOT




ELECTRICAL

Wattage	200W
Voltage	277-480V
Power factor	0.90
THD	15%
Operating temp	-30 to 50°C

CONSTRUCTION

Housing	Aluminum alloy
Finish	Black
IP rating	IP65
Weight	10.5 lbs
Carton qty	1
Carton weight	13.2 lbs
Carton dimensions	43.1 x 43.1 x 20.3 cm

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

