

200W High Bay, 120-277V



NEW HB7 series High Bay Ideal for warehouses, factories, and workshops



High grade aluminum body for superior heat dissipation

110° beam angle

Optical grade high impact glass for maximum light transmittance

1m power cord extension available



www.csc-led.com

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	27,506 lm
Efficacy	140.35 lm/W
CCT	5000K
CRI	80
L70 Life	60,000 hrs
Dimmable	0-10V
Warranty	5-year


APPROVALS AND LISTINGS

cUL	E482965
DLC Premium	PLPG2K02OF34

ILLUMINANCE AT A DISTANCE

Center Beam fc	Beam Wi	idth
32.9 fc	53.2 ft	52.7 ft
8.23 fc	106.4 ft	105.3 ft
3.66 fc	159.6 ft	158.0 ft
2.06 fc	212.8 ft	210.7 ft
1.32 fc	266.0 ft	263.3 ft
0.91 fc	319.2 ft	316.0 ft
	8.23 fc 3.66 fc 2.06 fc 1.32 fc	32.9 fc 53.2 ft 8.23 fc 106.4 ft 3.66 fc 159.6 ft 2.06 fc 212.8 ft 1.32 fc 266.0 ft

ISOCANDELA PLOT




ELECTRICAL

Wattage	200W
Voltage	120-277V
Power factor	0.90
THD	15%
Operating temp	-30 to 50°C

CONSTRUCTION

Housing	Aluminum alloy
Finish	Black
IP rating	IP65
Weight	10.5 lbs
Carton qty	1
Carton weight	13.2 lbs
Carton dimensions	43.1 x 43.1 x 20.3 cm

DIMENSIONS



Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitiam, BC V3C 6P8 | ordersbc@csc-led.com



8-540 Jamieson Parkway, Cambridge, ON Canada N3C 0G5 P: 519.880.9833 888.900.9885 E: info@csc-led.com orders@csc-led.com