

#### **FLM Series**

# NEW!



FLM-90W-3CCT-UD

#### Mini Flood Lights

Ideal for landscaping, patio, and security lighting, signs, and more

Watts	15W, 30W, 50W, 70W, 90W
Voltage	120-347V (15W: 120-277V)
Colour temp	Tunable (3000K, 4000K, 5000K) (15W: 4000K)
Lumens	1,603 lm to 11,700 lm
Lens	Polycarbonate
15W Mount	Knuckle* or Mount*
30W-90W Mount	Yoke Standard Slip Fitter**, Knuckle Mount**

# Concorde Series (FL04B)







Motion Sensor



Slip Fit (SF)



Pole Mount (PM)



Multi Mount (MM)

#### Concorde series Flood / Area Lights - NEW FL04B

Trunnion Standard - interchangeable mounting options (sold separately) Removable access plate. Prewired for optional motion sensor (sold separately)

Watts	60W, 80W, 100W, 150W, 200W, 240W, 300W	
Voltage	120-347V	
Colour temp	4000K, 5000K	
Lumens	8,123 lm to 41,344 lm	
Mounting	Trunnion, Slip Fit**, Pole Mount**, Multi Mount**, Yoke Mount***	
Finish colour	Bronze, White*	
Accessories**	Photocell and Receptacle, Remote Control, Motion Sensor	

# Solar Power

# Street Light (ST02)



ST02-50W-40K

# Solar Wall Pack (SWP01)



SWP01-5W-50K

# Solar Flood Light (SFL)



stocking items



SFL-10W-7200-50K

# Slim Design with low EPA wind resistance Twist lock photocell receptacle included

Watts	50W, 100W
Colour temp	4000K
Lumens	6,675 lm to 12,637 lm
Voltage	120-277V

A photocell (JL-205LV) or a Shorting Cap (JL-208) must be used (sold separately)

#### Solar with motion sensor

Quick and easy installation with no cords or wires. On/off motion sensor

Watts	5W
Colour temp	5000K
Lumens	450 lm
Accessory**	Lithium Battery

# Solar with dual motion sensors

Insulated for cold climates. 3 operating modes to choose from. 360° adjustable yoke

Watts	10W
Colour temp	5000K
Lumens	1,080 lm
Accessory**	Replaceable Lithium Battery

<sup>\*</sup> Not recommended for sustained ambient temperatures below -20°C

# High Bays

# HB7B Series

# NEW!



HB7B-150W-40K-UD-GL

# Available in 120-277V (Low Voltage) and 120-347V (Universal Driver)

Prewired centre mounted receptacle for easy installation of a twist on motion sensor. 10KV surge suppression built-in standard

Watts	100W, 150W, 200W, 240W, *300W	
Voltage	120-277V, 120-347V, 277-480V*	
Colour temp	4000K, 5000K	
Lumens	15,015 lm to 43,272 lm	
Lens	Tempered Glass	
Accessories**	Yoke Mount, Motion Sensor, Motion Sensor Remote, Frosted Lens, Aluminum Reflector, Polycarbonate Reflector, Bottom Cover, Wireguard	

# LHB2 Series



LHB2-110W-50K-UD

#### Energy efficient replacement for traditional fluorescent fixtures and HID high bays

Centre knockout allows for easy installation of optional motion sensor (sold separately)

Watts	110W, 165W, 220W, 300W
Voltage	120-347V
Colour temp	4000K, 5000K
Lumens	15,311m to 43,547 lm
Finish	White
Accessories**	Motion Sensor, Motion Sensor Remote, Wireguard, Mounting Bracket

# Wall Packs

# **WPX Series**

# NEW!



WPX-30W-3CCT-UD

#### The most versatile architectural wall pack in Canada

Colour tunable wall pack - ideal for outdoor mount applications including commercial and industrial buildings

Watts	30W, 50W, 80W, 100W, 120W
Voltage	120-347V
Colour temp	Tunable (3000K, 4000K, 5000K)
Lumens	4,075 lm to 13,000 lm
Finish colour	Black
Accessories**	Visor, Type IV Optics, Type V Optics

#### **AWP03 Series**

# NEW!



AWP03-40WS-40K-UD

#### Versatile wall pack that fits almost any outdoor lighting application

Ideal for building entrances, multi-use facilities, apartment buildings, institutions, schools, and more

Watts	20W, 10W-40W, 40W, 80W, 120W
Voltage	120-277V*, 120-347V
Colour temp	4000K
Lumens	2,593 lm to 15,702 lm
Finish colour	Bronze
Accessories**	Photocell*, Photocell Extension*





# CWP02 Series

#### While Supplies Last



CWP02-60W-40K

# **CWP03 Series**

#### While Supplies Last

NEW CWP04 Wall Packs

Expected Feb. 2021



CWP03-80W-50K

#### Classic style wall pack with glass lens

Die-cast aluminum body, purpose built driver inside

Watts	40W, 60W, 80W, 120W
Voltage	120-277V
Colour temp	4000K, 5000K
Lumens	5,627 lm to 17,453 lm
Finish colour	Bronze

#### High impact polycarbonate lens

Vandal resistant, LM80 tested Lumiled chips

Watts	40W, 60W, 80W, 120W
Voltage	120-277V, 277-480V
Colour temp	4000K, 5000K
Lumens	5,536 lm to 17,671 lm
Finish colour	Bronze

#### Rotatable (RWP)



RWP-40W-50K

# DLC PREMIUM - Rotatable modules allow for use as an uplight, downlight, or both\*\*\*. Ideal for security lighting, wall washing, flood lighting, and more

	v
Watts	25W, 40W, 60W, 80W
Voltage	120-277V
Colour temp	4000K, 5000K
Lumens	3,324 lm to 10,598 lm
25/40W	1 rotatable module
60/80W***	2 independent rotatable modules
Finish colour	Black
Accessory**	Extension Plate

# Wall Sconce (DWS)



DWS-15W-30K-BK



Light Covers

#### Decorative Wall Sconce

Choose from 3 looks to create your custom look. Suitable for indoor or outdoor applications

Watts	15W
Voltage	120-277V
Colour temp	3000K, 4000K
Lumens	1,300 lm
Weight	0.76 kg
Finish colour	Bronze, Black
Carton qty	12
Accessories**	Cover 1, Cover 2, Cover 4

# Mini Wall Packs (MWP2)



MWP2-15W-30K

#### Mini wall pack with big performance

Quick installation (with or without octagon box). Ideal for security lighting, commercial entrances, and more

Watts	15W, 20W
Voltage	120-277V
Colour temp	3000K, 4000K
Lumens	1,931 lm to 2,584 lm
Weight	1.98 lbs
Finish colour	Bronze
Operating temp	-40 to 45°C
Carton qty	10



# Troffers/Panels

# **Volumetric Troffers**



VOL24-40W-40K-UD

# Backlit Panel Light



PLBL14-50W-40K

#### DLC Premium - Damp Location Rated

Suitable for commercial and retail lighting areas, low glare frosted diffuser

Watts	30W, 40W
Voltage	120-347V
Colour temp	3500K, 4000K
Lumens	3,765 lm to 5,115 lm
Finish colour	White
Sizes	1'x4', 2'x2', 2'x4',

#### Low profile, high performance

Back mounted LED chips with superior lensing ensures even overlap and illumination

Watts	40W, 50W
Voltage	100-347V
Colour temp	3500K, 4000K, 5000K
Lumens	4,342 lm to 5,074 lm
Accessories**	Surface Mount Kit, Cable Kit
Sizes	1'x4', 2'x2', 2'x4',

# Explosion Proof / Hazloc

#### C1, D2, (Groups A,B,C,D)

Suitable for hazardous environments where flammable gases or vapours, flammable liquids, combustible dust and/or ignitable fibers may exist. Also suitable for wet locations, marine environments, and high vibration applications

# **EXPR Series**

NEW!



EXPR-100W-50K

Watts	60W, 100W, 150W
Voltage	120-277V
Colour temp	5000K
Lumens	8,870 lm to 23,894 lm
Finish colour	Orange
Operating temp	-40 to 55°C
Accessory**	Wire Guard

#### **EXPL Series**

NEW!



EXPL-40W-2FT-50K

Watts	40W, 80W
Voltage	120-277V
Colour temp	5000K
Lumens	5,881 lm to 11,202 lm
Finish colour	Orange
Operating temp	-40 to 60°C
Accessory**	Wire Guard

# CES Series



CES-J100

Watts	30W, 100W, 185W
Voltage	120-277V
Colour temp	5000K
Lumens	3,131 lm to 21,313 lm
Finish colour	White
Operating temp	-20 to 40°C

\*While supplies last





# Tri-proof



SL-A65F2-30-P

#### Ideal for workshops and work cells

Water-proof, dust-proof, damp-proof, and vapour-proof. Can be surface mounted or suspended

Watts	30W, 40W
Length	2ft, 4ft
Voltage	120-277V
Colour temp	5000K
Lumens	3,900 lm to 5,200 lm
Accessories**	Male & 3-pin connectors, Single ended cord, double ended cord, cable kits

# Canopy (CP)



CP40W-40K-WH

#### Suitable for wet locations

High impact polycarbonate lens. Hinged mounting plate for quick installation. Built-in surge protector

Watts	40W, 75W
Voltage	120-277V
Colour temp	4000K
Lumens	4,464 lm to 9,197 lm
Operating temp	-40 to 40° C
Finish Colour	White
Accessory**	Microwave Motion Sensor

# NEMA 4X Vapour Tight

#### NEW SIZESI



#### Ideal replacement for T8 Fixtures

One piece design and handle makes installation quick and easy

Watts	36W, 46W, 65W, 100W, 150W
Voltage	120-347V
Colour temp	4000K, 5000K, Tunable*
Lumens	5,605 lm to 20,400 lm
Length	4ft, 8ft*
Accessories**	Motion Sensor, Backup Battery

# **LED Strips**

# T-Grid Integrated Luminare



TBAR4-DM-40K

#### Available in 2 ft and 4 ft sizes

Slim profile with a frosted lens. Creates an architectural statement while distributing the lumens over the entire space

Watts	10W, 20W
Voltage	120-277V
Colour temp	3500K, 4000K
Lumens	1,300 lm to 2,600 lm
Accessory*	Power supply

# Tunable Linear Strip (ST4)



ST4-32W-3CCT-UD

#### Quickest row mount fixture on the market

Tool-less entry, 120-347V, external CCT selector switch

Watts	32W
Voltage	120-347V
Colour temp	CCT (35K, 40K, 50K)
Lumens	4,192 lm
Accessories**	Aircraft Cable, Connector, Motion Sensor, Emergency Battery Backup

# Shop Light



TC-SL2040BHM-50

#### Ideal for garages workshops and more

Instant on to full brightness with low glare and a 1m chain included. Linkable up to 8 units, includes row mount connector

Watts	40W
Voltage	120V
Colour temp	5000K
Lumens	5,269 lm
Housing	Plastic and Aluminum



# www.csc-led.com

# Area/Security/Work Lights

# Security Light (SS)



SS-HG70-20W

#### With dual-head and motion sensor

150° detection zone and adjustable detection sensitivity

Watts	20W
Voltage	120V
Colour temp	5000K
Lumens	1,815 lm
Finish	White, Black
Includes	Motion Sensor

# Temporary Work Light String



TWL-S-20WX5-50K

#### Comes with 5 lights and 10 ft cord

Ideal for subway construction, factory/residential renovations, and more

Watts	20W x 5
Voltage	120V
Colour temp	5000K
Lumens	12,500 lm
Housing	PC and Aluminum
Colour	Orange

# Temporary Work Light



TWL-100W-50K

#### Waterproof isolated driver

Ideal for all new construction and temporary lighting applications

Watts	100W
Voltage	120V
Colour temp	5000K
Lumens	12,500 lm
Equal to	250W HID
Accessory**	Tripod

# Pole Top

# Pole Top Area Light (PTA02)



PTA02-100W-40K

# Horticultural

# Linear Grow Light



LGL-1200-53W

#### Elegant look and design

Ideal for parking lots, pathways, parks, retail settings, and more, Complete with polyester powder coat finish, twist lock photocell receptacle, and high efficiency optics

Watts	35W, 55W, 75W, 100W, 150W
Voltage	120-277V
Colour temp	4000K, Tunable (3000K, 4000K, 5000K)*
Lumens	3,848 lm to 18,686 lm
Includes	Twist lock photocell receptacle, Photocell

Shorting cap sold separately

#### Full spectrum output for everything your plant needs

Ideal for vertical farming and the growth of fruit products, vegetables, and medical cannabis

Watts	53W
Beam angle	120°
Housing	Aviation Aluminum
Unit Weight	7.1lbs

Please email or call for more information about this fixture and other grow light fixtures available.



# Lamps

# Corn Lamps



CLW08-100WBCA1-E50K

#### Suitable for enclosed fixtures

Replacement lamp for MH and HPS. High efficiency with 4.5KV surge suppression

Watts	15W, 19W, 24W, 30W, 36W, 54W, 75W, 100W, 120W
Voltage	120-277V
Colour temp	5000K
Lumens	12,083 lm to 13,667 lm
Base	E26*, E39*

# Paddle Lamps (CLH)



CLH-54WA1

#### Rated for enclosed fixtures

LED replacement lamps for directional MH and HPS. Ideal for use in area lights, flood lights, and wall packs

Watts	27W, 36W, 54W, 75W
Voltage	120-277V
Colour temp	5000K
Lumens	3,032 lm to 8,615 lm
Base	E26*, E39*

\*SELECT PRODUCTS ONLY. | \*\*ORDER SEPARATELY.

THE INFORMATION PROVIDED IN OUR PRINT CATALOGUES AND ON OUR WEBSITE HAS BEEN GATHERED AND ASSEMBLED WITH EVERY EFFORT MADE TO VERIFY THE ACCURACY OF THE CONTENT; HOWEVER, MISTAKES CAN HAPPEN. THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE.

IF YOU HAVE ANY QUESTIONS OR COMMENTS, PLEASE REACH OUT TO US AT MARKETING@CSC-LED.COM

# Choose Wisely - Choose & CSCLED

#### **DISTRIBUTORS**

Set up your online account to view pricing, product availability, and to place your order

#### **CONTRACTORS**

Contact your preferred electrical wholesaler for more information and to place your order

Visit www.csc-led.com to learn more about our products, technical specifications, IES files, product availability, certifications, customer testimonials, and more.

"Great price point with the quality of the big companies."

- Verified Purchaser (ON) July 2020 "Easy to order, great prices, and fast shipping!"

> - Verified Purchaser (BC) August 2020

"Very friendly customer service and prompt communication."

 Verified Purchaser (ON) September 2020

